

## JOTUN Premium mur filler

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

|                                      |                            |
|--------------------------------------|----------------------------|
| <b>Product name</b>                  | : JOTUN Premium mur filler |
| <b>Product code</b>                  | : 100                      |
| <b>Product description</b>           | : Waterborne paint.        |
| <b>Product type</b>                  | : Liquid.                  |
| <b>Other means of identification</b> | : Not available.           |

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Consumer use: Apply this product only as specified on the label.

#### 1.3 Details of the supplier of the safety data sheet

Jotun A/S  
P.O.Box 2021  
3202 Sandefjord  
Norway  
Tel: + 47 33 45 70 00  
Fax: +47 33 45 72 42  
E-mail: SDSJotun@jotun.no

Jotun Paints (Europe) Ltd.  
Stather Road  
Flixborough, Scunthorpe  
North Lincolnshire  
DN15 8RR  
England

Tel: +44 17 24 40 00 00  
Fax: +44 17 24 40 01 00

#### 1.4 Emergency telephone number

##### National advisory body/Poison Centre

**Telephone number** : Contact NHS Direct; phone 0845 4647 or 111. Open 24/7.

##### Supplier

**Telephone number** : +47 33 45 70 00 Jotun Norway (head office)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

##### Classification according to UK CLP/GHS

Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

**Signal word** : No signal word.

**Hazard statements** : H412 - Harmful to aquatic life with long lasting effects.

##### Precautionary statements

**General** : P102 - Keep out of reach of children.

**Prevention** : P273 - Avoid release to the environment.

**Response** : Not applicable.

**Storage** : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

JOTUN Premium mur filler

## SECTION 2: Hazards identification

**Supplemental label elements** : EUH208 - Contains 3-iodo-2-propynyl butylcarbamate (IPBC), 1,2-benzisothiazol-3(2H)-one (BIT) and C(M)IT/MIT (3:1). May produce an allergic reaction.  
EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Additional information** : Contains less than 0.01% Methylisothiazolinone (MIT).  
Contains film preservative: DCOIT.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Special packaging requirements

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

| Product/ingredient name                 | Identifiers   | %       | Classification   | Type           |
|---|---|---------|--|----------------|
| Calc (non-asbestos form)                | EC: 238-877-9<br>CAS: 14807-96-6  | ≤10     | Not classified.  | [2]            |
| titanium dioxide                        | REACH #:<br>01-2119489379-17<br>EC: 236-675-5<br>CAS: 13463-67-7<br>Index: 022-006-00-2 | ≤5      | Carc. 2, H351<br>(inhalation)  | [1] [2]<br>[*] |
| 3-iodo-2-propynyl butylcarbamate (IPBC) | EC: 259-627-5<br>CAS: 55406-53-6<br>Index: 616-212-00-7                                 | ≤0.3    | Acute Tox. 4, H302<br>Acute Tox. 3, H331<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>STOT RE 1, H372<br>(trachea)<br>Aquatic Acute 1, H400<br>(M=10)<br>Aquatic Chronic 1,<br>H410 (M=1)                            | [1]            |
| C(M)IT/MIT (3:1)                        | REACH #:<br>01-2120764691-48<br>CAS: 55965-84-9<br>Index: 613-167-00-5                  | <0.0015 | Acute Tox. 3, H301<br>Acute Tox. 2, H310<br>Acute Tox. 2, H330<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1A, H317<br>Aquatic Acute 1, H400<br>(M=100)<br>Aquatic Chronic 1,<br>H410 (M=100)<br>EUH071 | [1]            |

**SECTION 3: Composition/information on ingredients**

|  |  |  |   |  |
|--|--|--|---|--|
|  |  |  | <b>See Section 16 for the full text of the H statements declared above.</b> |  |
|--|--|--|---|--|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq 10 \mu\text{m}$  not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

**4.2 Most important symptoms and effects, both acute and delayed**

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-iodo-2-propynyl butylcarbamate (IPBC), 1,2-benzisothiazol-3(2H)-one (BIT), C(M)IT/MIT (3:1). May produce an allergic reaction.

**Over-exposure signs/symptoms**

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

See Technical Data Sheet / packaging for further information.

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name                      | Exposure limit values   |
|--|---|
| calc (non-asbestos form)<br>titanium dioxide | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b><br>TWA: 1 mg/m <sup>3</sup> 8 hours. Form: respirable dust<br><b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b><br>TWA: 4 mg/m <sup>3</sup> 8 hours. Form: respirable<br>TWA: 10 mg/m <sup>3</sup> 8 hours. Form: total inhalable |

#### Biological exposure indices

No exposure indices known.

- Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

| Product/ingredient name  | Type | Exposure              | Value                  | Population         | Effects  |
|--------------------------|------|-----------------------|------------------------|--------------------|----------|
| calc (non-asbestos form) | DNEL | Short term Inhalation | 1.08 mg/m <sup>3</sup> | General population | Systemic |
|                          | DNEL | Long term Inhalation  | 1.08 mg/m <sup>3</sup> | General population | Systemic |
|                          | DNEL | Short term Inhalation | 1.8 mg/m <sup>3</sup>  | General population | Local    |
|                          | DNEL | Long term Inhalation  | 1.8 mg/m <sup>3</sup>  | General population | Local    |
|                          | DNEL | Short term Inhalation | 2.16 mg/m <sup>3</sup> | Workers            | Systemic |
|                          | DNEL | Long term Inhalation  | 2.16 mg/m <sup>3</sup> | Workers            | Systemic |

## SECTION 8: Exposure controls/personal protection

|   |                  |                                |                             |                        |                       |
|---|------------------|--------------------------------|-----------------------------|------------------------|-----------------------|
| 3-iodo-2-propynyl butylcarbamate (IPBC) | DNEL             | Inhalation<br>Long term Dermal | 2.27 mg/<br>cm <sup>2</sup> | General<br>population  | Local                 |
|   | DNEL             | Short term<br>Inhalation       | 3.6 mg/m <sup>3</sup>       | Workers                | Local                 |
|   | DNEL             | Long term<br>Inhalation        | 3.6 mg/m <sup>3</sup>       | Workers                | Local                 |
|   | DNEL             | Long term Dermal               | 4.54 mg/<br>cm <sup>2</sup> | Workers                | Local                 |
|   | DNEL             | Long term Dermal               | 21.6 mg/<br>kg bw/day       | General<br>population  | Systemic              |
|   | DNEL             | Long term Dermal               | 43.2 mg/<br>kg bw/day       | Workers                | Systemic              |
|   | DNEL             | Short term Oral                | 160 mg/kg<br>bw/day         | General<br>population  | Systemic              |
|   | DNEL             | Long term Oral                 | 160 mg/kg<br>bw/day         | General<br>population  | Systemic              |
|   | DNEL             | Long term<br>Inhalation        | 0.023 mg/<br>m <sup>3</sup> | Workers                | Systemic              |
|   | DNEL             | Short term<br>Inhalation       | 0.07 mg/m <sup>3</sup>      | Workers                | Systemic              |
|   | DNEL             | Short term<br>Inhalation       | 1.16 mg/m <sup>3</sup>      | Workers                | Local                 |
|   | DNEL             | Long term<br>Inhalation        | 1.16 mg/m <sup>3</sup>      | Workers                | Local                 |
|   | DNEL             | Long term Dermal               | 2 mg/kg<br>bw/day           | Workers                | Systemic              |
|   | C(M)IT/MIT (3:1) | DNEL                           | Long term<br>Inhalation     | 0.02 mg/m <sup>3</sup> | General<br>population |
| DNEL                                    |                  | Long term<br>Inhalation        | 0.02 mg/m <sup>3</sup>      | Workers                | Local                 |
| DNEL                                    |                  | Short term<br>Inhalation       | 0.04 mg/m <sup>3</sup>      | General<br>population  | Local                 |
| DNEL                                    |                  | Short term<br>Inhalation       | 0.04 mg/m <sup>3</sup>      | Workers                | Local                 |
| DNEL                                    |                  | Long term Oral                 | 0.09 mg/<br>kg bw/day       | General<br>population  | Systemic              |
| DNEL                                    |                  | Short term Oral                | 0.11 mg/<br>kg bw/day       | General<br>population  | Systemic              |

### PNECs

No PNECs available

### 8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### Skin protection

##### Hand protection

## SECTION 8: Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

### Gloves

Wear suitable gloves tested to ISO 374-1:2016.

May be used, gloves(breakthrough time) 4 - 8 hours: polyvinyl alcohol (PVA) (> 0.3 mm), nitrile rubber (> 0.4 mm), neoprene (> 0.35 mm)

Recommended, gloves(breakthrough time) > 8 hours: PVC (> 0.5 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits. By spraying : particulate filter (FFP2 / N95). In confined spaces, use compressed-air or fresh-air respiratory equipment.
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : White.
- Odour** : Characteristic.
- Odour threshold** : Not applicable.
- Melting point/freezing point** : 0
- Initial boiling point and boiling range** : Lowest known value: 100°C (212°F) (water). Weighted average: 115.89°C (240.6°F)
- Flammability** : Not applicable.
- Upper/lower flammability or explosive limits** : 0.6 - 4.2%
- Flash point** : Not applicable.
- Auto-ignition temperature** : Not applicable.
- Decomposition temperature** : Not available.
- pH** : 8.3 to 9.3
- Viscosity** : Kinematic (40°C): >20.5 mm<sup>2</sup>/s

JOTUN Premium mur filler

## SECTION 9: Physical and chemical properties

**Partition coefficient: n-octanol/ water** : Not available.

**Vapour pressure** : Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.88 kPa (21.6 mm Hg) (at 20°C)

**Evaporation rate** : 0.36 (water) compared with butyl acetate

**Vapour density** : Highest known value: 7.5 (Air = 1) (propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol).

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

### Particle characteristics

**Median particle size** : Not applicable.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-iodo-2-propynyl butylcarbamate (IPBC), 1,2-benzisothiazol-3(2H)-one (BIT), C(M)IT/MIT (3:1). May produce an allergic reaction.

### Acute toxicity

| Product/ingredient name                 | Result    | Species | Dose       | Exposure |
|---|-----------|---------|------------|----------|
| 3-iodo-2-propynyl butylcarbamate (IPBC) | LD50 Oral | Rat     | 1470 mg/kg | -        |
| C(M)IT/MIT (3:1)                        | LD50 Oral | Rat     | 53 mg/kg   | -        |

### Acute toxicity estimates

| Product/ingredient name                 | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| JOTUN Premium mur filler                | N/A          | N/A            | N/A                      | N/A                         | 222.2                               |
| 3-iodo-2-propynyl butylcarbamate (IPBC) | 500          | N/A            | N/A                      | N/A                         | 0.5                                 |
| C(M)IT/MIT (3:1)                        | 53           | 50             | N/A                      | 0.5                         | N/A                                 |

### Irritation/Corrosion



JOTUN Premium mur filler

## SECTION 11: Toxicological information

| Product/ingredient name  | Result                                  | Species                                     | Score  | Exposure      | Observation |
|--|---|---|--------|---------------|-------------|
| Titanium dioxide<br>3-iodo-2-propynyl<br>butylcarbamate (IPBC) | Skin - Mild irritant<br>Eyes - Irritant | Human<br>Mammal -<br>species<br>unspecified | -<br>- | 72 hours<br>- | -<br>-      |

### Sensitisation

| Product/ingredient name                    | Route of exposure | Species                         | Result      |
|--|-------------------|---------------------------------|-------------|
| 3-iodo-2-propynyl<br>butylcarbamate (IPBC) | skin              | Mammal - species<br>unspecified | Sensitising |
| C(M)IT/MIT (3:1)                           | skin              | Mammal - species<br>unspecified | Sensitising |

### Mutagenicity

No known significant effects or critical hazards.

### Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

No known significant effects or critical hazards.

### Reproductive toxicity

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

### Teratogenicity

No known significant effects or critical hazards.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name                 | Category   | Route of exposure | Target organs |
|---|------------|-------------------|---------------|
| 3-iodo-2-propynyl butylcarbamate (IPBC) | Category 1 | -                 | trachea       |

### Aspiration hazard

Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.

**Inhalation** : No specific data.

**Skin contact** : No specific data.

**Ingestion** : No specific data.

**General** : No known significant effects or critical hazards.

**Other information** : None identified.

JOTUN Premium mur filler

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

| Product/ingredient name  | Result                                  | Species   | Exposure  |          |
|--------------------------|---|---|---|----------|
| Titanium dioxide         | Acute LC50 3 mg/l Fresh water           | Crustaceans - Water flea - Ceriodaphnia dubia - Neonate | 48 hours  |          |
|                          | Acute LC50 6.5 mg/l Fresh water         | Daphnia - Water flea - Daphnia pulex - Neonate          | 48 hours  |          |
|                          | Acute LC50 >1000000 µg/l Marine water   | Fish - Mummichog - Fundulus heteroclitus                | 96 hours  |          |
|                          | 3-iodo-2-propynyl butylcarbamate (IPBC) | Acute EC50 0.022 mg/l                                   | Algae - Algae - Scenedesmus subspicatus   | 72 hours |
|                          |   | Acute EC50 0.16 mg/l                                    | Crustaceans - Daphnia - Daphnia magna   | 48 hours |
|                          |   | Acute LC50 0.067 mg/l                                   | Fish - Trout - Oncorhynchus mykiss  | 96 hours |
|                          | C(M)IT/MIT (3:1)                        | Chronic NOEC 70 ppb Fresh water                         | Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
|                          |   | Acute EC50 0.048 mg/l                                   | Algae - Pseudokirchneriella subcapitata   | 72 hours |
|                          |   | Acute EC50 0.0052 mg/l                                  | Algae - Skeletonema costatum  | 48 hours |
|                          |   | Acute EC50 0.1 mg/l                                     | Daphnia - Daphnia magna   | 48 hours |
| Acute LC50 0.22 mg/l     |   | Fish - Trout - Oncorhynchus mykiss                      | 96 hours  |          |
| Acute NOEC 0.00064 mg/l  |   | Algae - Skeletonema costatum                            | 48 hours  |          |
| Chronic NOEC 0.0012 mg/l |   | Algae - Pseudokirchneriella subcapitata                 | 72 hours  |          |
| Chronic NOEC 0.004 mg/l  |   | Daphnia - Daphnia magna                                 | 21 days   |          |
| Chronic NOEC 0.098 mg/l  | Fish - Oncorhynchus mykiss              | 28 days   |   |          |

**Conclusion/Summary** : This material is harmful to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

| Product/ingredient name                 | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| 3-iodo-2-propynyl butylcarbamate (IPBC) | -                 | -          | Readily          |
| C(M)IT/MIT (3:1)                        | -                 | -          | Not readily      |

### 12.3 Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF  | Potential |
|-------------------------|--------------------|------|-----------|
| C(M)IT/MIT (3:1)        | -                  | 3.16 | low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### Waste catalogue

| Waste code | Waste designation  |
|------------|--|
| 08 01 12   | waste paint and varnish other than those mentioned in 08 01 11 |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | Waste catalogue  |
|-------------------|--|
| CEPE Guidelines   | 15 01 10* packaging containing residues of or contaminated by hazardous substances |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|  | ADR/RID        | ADN            | IMDG           | IATA           |
|--|----------------|----------------|----------------|----------------|
| <b>14.1 UN number</b>                  | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| <b>14.2 UN proper shipping name</b>    | -              | -              | -              | -              |
| <b>14.3 Transport hazard class(es)</b> | -              | -              | -              | -              |
| <b>14.4 Packing group</b>              | -              | -              | -              | -              |
| <b>14.5 Environmental hazards</b>      | No.            | No.            | No.            | No.            |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### UK (GB)/REACH

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

###### Ozone depleting substances

Not listed.

###### Prior Informed Consent (PIC)

Not listed.

###### Persistent Organic Pollutants

Not listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

###### Seveso Directive

This product is not controlled under the Seveso Directive.

###### EU regulations

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

###### International regulations

###### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

###### Montreal Protocol

Not listed.

###### Stockholm Convention on Persistent Organic Pollutants

Not listed.

###### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

###### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

JOTUN Premium mur filler

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
 GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = GB CLP-specific Hazard statement  
 N/A = Not available  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification

| Classification          | Justification      |
|-------------------------|--------------------|
| Aquatic Chronic 3, H412 | Calculation method |

### Full text of abbreviated H statements

|        |   |
|--------|---|
| H301   | Toxic if swallowed.   |
| H302   | Harmful if swallowed.   |
| H310   | Fatal in contact with skin.                                     |
| H314   | Causes severe skin burns and eye damage.                        |
| H317   | May cause an allergic skin reaction.                            |
| H318   | Causes serious eye damage.                                      |
| H330   | Fatal if inhaled.   |
| H331   | Toxic if inhaled.   |
| H351   | Suspected of causing cancer.                                    |
| H372   | Causes damage to organs through prolonged or repeated exposure. |
| H400   | Very toxic to aquatic life.                                     |
| H410   | Very toxic to aquatic life with long lasting effects.           |
| H412   | Harmful to aquatic life with long lasting effects.              |
| EUH071 | Corrosive to the respiratory tract.                             |

### Full text of classifications

|                   |   |
|-------------------|---|
| Acute Tox. 2      | ACUTE TOXICITY - Category 2                                     |
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                     |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1                  |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1                 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3                 |
| Carc. 2           | CARCINOGENICITY - Category 2                                    |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Skin Corr. 1B     | SKIN CORROSION/IRRITATION - Category 1B                         |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                                 |
| Skin Sens. 1A     | SKIN SENSITISATION - Category 1A                                |
| STOT RE 1         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |

Date of printing : 21.04.2023

Date of issue/ Date of revision : 21.04.2023

Date of previous issue : 30.03.2023

Version : 1.02

### Notice to reader

JOTUN Premium mur filler

## SECTION 16: Other information

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.